



CHONGQING CUMMINS ENGINE PERFORMANCE CURVE

Engine Model
NTAA855-G7

Curve No.
C-164E

Rev
03

CPL Code
CQ122



Data Sheet
DS-164E

Description
FR-164E

Date
2006-9-22

Displacement: **14L** [855 in.³] Cylinders: **6** Fuel System: **PT**
Bore: **140mm** [5.50 in.] Speed: **1500 r/min** Cfg. Number: **D093629DX02**
Stroke: **152mm** [6.00in.] Aspiration: **Turbocharged & Air-Air Cooled**

Standby Power		Prime Power		Continuous Power	
kW	HP	kW	HP	kW	HP
377	505	343	460		



	Output Power		Fuel Consumption		Fuel Rate
	HP	kW	kg/h	L/h	g/kW·h
110%	505	377	78.0	94.0	206.9
100%	460	343	70.9	85.4	206.7
75%	345	257	53.7	64.7	208.7
50%	230	172	37.0	44.6	215.7
25%	115	86	20.4	24.6	237.9
10%	46	34	9.8	11.8	285.7

All data is based on :

- Engine Operating with fuel system, water pump, lubricating oil pump, air cleaner and exhaust silencer, fan, and optional driven components.
- Engine operating with fuel corresponding to grade No.2-D per ASTM D975.
- ISO 3046, Part1, Standard Reference Conditions of : Barometric Pressure:100kPa(29.5in.Hg); Altitude: 110m (361ft.); Air Temperature: 25℃ (77°F) ; Relative Humidity: 30% .

All Data is Subject to Change Without Notice - contact CCEC for latest data . Tel : 86-400-889-9990



Chongqing Cummins Engine Co. Ltd.

Engine Data Sheet

MODEL: NTAA855-G7
CONFIGURATION NO.: D093629DX02
CPL NUMBER: CQ122

DATA SHEET: DS-164E
PERFORMANCE CURVE: C-164E
INSTALLATION DIAGRAM: 4061323

PRIME POWER 460 HP (343 kW) at 1500 r/min
STANDBY POWER: 505 HP (377 kW) at 1500 r/min

DATE: 2006-9-22
REVISION: 04

GENERAL ENGINE DATA

Type.....	4-Cycle;In-line;6-Cylinder	
Aspiration	Turbocharged,Air-Air Cooled	
Bore x Stroke - in.×in. (mm×mm).....	5.5 ×6	(140 × 152)
Displacement - in. ³ (L).....	855	(14)
Compression Ratio	14.0:1	
Firing Order	1-5-3-6-2-4	
Dry Weight		
--Engine Only - lb. (kg).....	2800	(1270)
Wet Weight		
--Engine Only - lb. (kg).....	2910	(1320)
Moment of Inertia of Rotating Components - With FW1109 flywheel - lb.·ft. ² (kg·n	118.5	(4.99)
Center of Gravity from Rear Face of Flywheel Housing - in.(mm)	27.7	(704)
Center of Gravity Above Crankshaft Centerline - in.(mm)	5.5	(140)

ENGINE MOUNTING

Maximum Allowable Bending Moment at Rear Face of Block - lb.·ft. (N·m).....	1000	(1356)
---	------	----------

EXHAUST SYSTEM

Maximum Allowable Back Pressure - in.Hg (kPa).....	3.0	(10)
Standard Exhaust Pipe Diameter - in. (mm).....	5.0	(127)

AIR INDUCTION SYSTEM

Maximum Allowable Intake Air Restriction		
--With Clean Filter Element - in. H ₂ O (kPa).....	15	(3.74)
--With Dirty Filter Element - in. H ₂ O (kPa)	25	(6.22)
Maximum Intake Pressure Fall from Turbo to Intake Manifold - PSI (kPa).....	5.0	(17)
Maximum Intake Manifold Temperature Rise - °F (°C).....	43	(24)
Minimum Dirt Holding Capacity - g/CFM (g/L/s).....	25	(53)
Maximum Allowable Intake Air Temperature ΔT - °F (°C).....	30	(17)

COOLING SYSTEM

Coolant Capacity - Engine Only - U.S. gal (L).....	5.5	(20.8)
- With Radiator - U.S. gal (L).....	16.0	(60.6)
Maximum Coolant Friction Head External to Engine - PSI (kPa).....	6	(41)
Maximum Static Head of Coolant (exclusive of Pressure Cap) - PSI (kPa)	15	(103)
Maximum Static Head of Coolant Above Engine Crank Centerline -ft. (m)	46	(14.0)
Standard Thermostat (Modulating) Range - °F (°C)	180 - 202	(82 - 94)
Minimum Allowable Pressure Cap -PSI (kPa).....	7.0	(48.2)
Maximum Coolant Temperature - °F (°C).....	205	(96)
Maximum Top Tank Temperature - °F (°C).....	212	(100)
Minimum Top Tank Temperature - °F (°C).....	160	(71)
Minimum Coolant Expansion Space - % of System Capacity	5	
Minimum Coolant Makeup Capacity - U.S. gal (L).....	1.1	(4.2)

LUBRICATION SYSTEM

Oil Pressure @ Idle Speed - PSI (kPa).....	15 Min	(103) Min
@ Governed Speed - PSI (kPa).....	35-50	(241 - 345)
Maximum Allowable Oil Temperature - °F (°C).....	250	(121)
Maximum Oil Consumption - U.S.qt./h (L/h).....	0.25	(0.24)
Oil Pan Capacity - Low / High - U.S. gal. (L).....	7.5 / 9.5	(28.4 / 36.0)
Total System Capacity - U.S. gal. (L).....	10.2	(38.6)
Angularity of Oil Pan - Front Down/Front Up/Side to Side.....	38°/38°/38°	

FUEL SYSTEM

Type Injection System.....	Direct Injection Cummins PT	
Maximum Allowable Restriction to Fuel Pump		
-- With Clean Fuel Filter - in.Hg (kPa).....	4.0	(13.5)
-- With Dirty Fuel Filter - in.Hg (kPa).....	8.0	(27.1)
Maximum Allowable Head on Injector Return Line		
-- With Check Valve - in.Hg (kPa).....	6.5	(22.0)
-- Without Check Valve - in.Hg (kPa).....	2.5	(8.5)
Minimum Fuel Supply Line Size - in. (mm).....	0.625	(16)
Minimum Fuel Return Line Size - in. (mm).....	0.5	(13)
Maximum Fuel Pump Supply - U.S.gal/h (L).....	98	(371)
Fuel Rail Pressure - PSI (kPa).....	149	(1028)
Maximum Fuel Temperature °F (°C).....	160	(71)

ELECTRICAL SYSTEM

Minimum Recommended Battery Capacity (24V)	
-- Cold Soak (No Load) - CCA.....	900
- Minimum Reserved Capacity - CCA.....	320
-- Cold Soak (With Load) - CCA.....	900
- Minimum Reserved Capacity - CCA.....	320
Maximum Allowable Resistance of Cranking Circuit - ohm.....	0.002
Standard Cranking Motor (Heavy Duty , Positive Engagement) - volt.....	24
Standard Battery Charging System , Negative Ground - ampere.....	35

PERFORMANCE DATA

Idle Speed - r/min	575 - 650	
Maximum No-Load Governed Speed - r/min	1800	
Maximum over Speed Capability - r/min	2700	
Minimum Crankshaft Rotation for unaided Cold Start - r/min.....	150	
Minimum Torque for unaided Cold Start - lb.·ft. (N·m).....	375	(509)
Exhaust Sound Pressure at 1m from Exhaust Outlet -1500r/min -dBA.....	N/A	

All data is based on :

--Engine Operating with fuel system, water pump, lubricating oil pump, air cleaner and exhaust silencer, fan, and optional driven components.

--Engine operating with fuel corresponding to grade No.2-D per **ASTM D975**.

--**ISO 3046**, Part1, Standard Reference Conditions of : Barometric Pressure:100kPa(29.5in.Hg); Altitude: 110m (361ft.); Air Temperature: 25°C (77°F) ; Relative Humidity: 30% .

--This Data Sheet includes both air-cooled (Fan/Radiator) & raw water cooled (Heatexchanger/Raw Water Pump) type engine.

	Prime Power		Standby Power	
	50Hz		50Hz	
	1500		1500	
Governed Engine Speed - r/min.....				
Gross Engine Power Output - HP (kW)	460	(343)	505	(377)
Torque lb.-ft. (N-m).....	1611	(2184)	1770	(2400)
Brake Mean Effective Pressure - PSI (kPa)	284	(1960)	312	(2154)
Piston Speed - ft./min (m/s).....	1500	(7.62)	1500	(7.62)
Friction Horsepower - HP (kW).....	30	(22)	30	(22)
Intake Air Flow - CFM (L/s)	1081	(510)	1028	(485)
Engine Water Flow - GPM (L/min.)	79	(5)	79	(5)
Raw Water Flow - GPM (L/s)	54	(3.4)	54	(3.4)
Fuel Consumption - U.S.gal/h (L/h).....	22.6	(86)	24.8	(94)
Oil Flow - GPM (L/s)	35	(2.2)	35	(2.2)
Exhaust Gas Temperature (After Turbine) - °F (°C).....	843	(451)	926	(497)
Exhaust Gas Flow (After Turbine) - CFM (L/s).....	2432	(1150)	2313	(1090)
Air to Fuel Ratio.....	28.3 : 1		24.5 : 1	
Heat Radiation - BTU (kW).....	2440	(43)	2680	(47)
Heat Rejection to Coolant - BTU (kW).....	14640	(257)	16090	(283)
Heat Rejection to Ambient - BTU (kW).....	12200	(214)	13410	(236)

Engine Model: NTAA855-G7

Data Sheet: DS-164E

Date: 2006-9-22

CHONGQING CUMMINS ENGINE CO. LTD.

CHONGQING, CHINA, 400031

All Data is Subject to Change Without Notice - contact CCEC for most recent data . Tel : 86-400-889-9990